

600 SERIES

DOOR CLOSER



- Certifications**
 - UL listed
 - 5 Year limited warranty
- Power Size**
 - Fixed power size 2 or 3
 - See selection guide for details*
- Body Material**
 - Cast aluminum alloy, painted finish
- Mechanism**
 - Hydraulic rack and pinion
- Fluid**
 - Non-gumming hydraulic fluid
- Adjustments**
 - Sweep speed valve
 - Latching speed valve
 - Cushioning backcheck valve – option
- Cover**
 - Plastic pinion cap, painted finish

- Handing**
 - Non-handed
- Opening**
 - 180° maximum
- Mounting**
 - Tri-pack: regular¹, top jamb¹ or parallel arm²
 - Maximum reveal: 1 3/4" (44.5 mm)
 - (1) Arm shoe allows ±7.5% power adjustment*
 - (2) May reduce spring power efficiency by 25%*
- Hardware**
 - Wood & machine screws
- Finish**
 - AL–Aluminum, painted;
 - BP–Brass, plated
 - Other finishes available by special order*


652	AL
MODEL	FINISH

SEE SELECTION GUIDE FOR DETAILS

SELECTION GUIDE

MODEL	POWER SIZE	WEIGHT CAPACITY ¹	MAX. DOOR ²		BACKCHECK	HOLD OPEN	DELAYED ACTION	FINISH	/CASE
			WIDTH	HEIGHT					
652	2	55-95 (25-45)	36 (914)	82 (2100)	—	—	—	AL, BP	10
653	3	85-145 (40-65)	38 (965)	82 (2100)	—	—	—	AL	10

(1) WEIGHT CAPACITY RANGE IN POUNDS (KILOGRAMS) (2) MAXIMUM DOOR WIDTH/HEIGHT IN INCHES (MILLIMETRES)



MODEL	A	B	C	D	E
652	3/4 (19)	6 5/8 (168)	1 23/32 (43.5)	7 5/16 (186)	2 5/8 (67)
653	3/4 (19)	8 1/8 (206)	1 3/4 (45)	8 25/32 (223)	2 27/32 (72)

IN (MM)