



- Certifications**
- Conforms to ANSI/BHMA A156.3, Grade 2
 - UL listed, Panic Exit
 - UL listed, up to 90 min. Fire Exit
 - 1 Year limited warranty

- Rail Assembly**
- Steel rail assembly
 - Stainless steel assembly (32D finish)
 - Field sizable

- Handing**
- Non-handed

- Door Width**
- 28–38" (711–965 mm)
 - 36–48" (914–1219 mm)* – option
- (*) Panic Exit models only

- Door Thickness**
- 1 3/4" (45.5 mm)

- Stile Width**
- 4" (106.1 mm) minimum
- Measured from door edge

- Projection**
- 2 9/16" (65 mm) from door surface

- Latchbolt**
- Stainless steel, 3/4" (19 mm) throw
 - Deadlatch

- Strike**
- Cast iron, standard type #8000S
- Other strikes available

- Dogging**
- For Panic Exit models only
 - Hex key dogging

- Hardware**
- Machine and wood screws
 - Sex nuts & thru-bolts¹ – available

(1) Required for non-reinforced hollow metal doors, included with Fire Exit models

Electrical Options

- Trims**
- Lever, knob, pull, and handleset trims available
- Sold separately, see 8500 Trims & Accessories

- Finish**
- 28–Aluminum, painted; 3–Polished brass; 32D–Satin stainless steel
- Other finishes available by special order


8500	–	32D	48
MODEL ¹		FINISH	OPTION

(1) SEE SELECTION GUIDE (2) OPTION: 48 –FOR DOORS 36-48X96IN (914-1219X2438MM)

SELECTION GUIDE

MODEL		DOOR WIDTH ¹	DOGGING	FINISH	/CASE
8500	Panic Exit Hardware, Rim device	28–38 (711–965)	•	28, 3, 32D	4
8500 -48		36–48 (914–1219)	•	28, 32D	4
8500F	Fire Exit Hardware ² Rim device	28–38 (711–965x2134)	—	28, 3, 32D	4

(1) RECOMMENDED DOOR WIDTH, IN (MM), FOR NON-STANDARD SIZES OR INSTALLATIONS PLEASE CONTACT. (2) FIRE EXIT HARDWARE MUST BE INSTALLED ON FIRE EXIT LABELLED DOORS.



MODEL	A	B	C	D	E ¹	F
8500 / 8500F	2 ⁹ / ₁₆ (65)	7 ¹¹ / ₁₆ (195)	2 (50.8)	20 ¹ / ₄ (514)	33 ¹ / ₄ (845)	1 ¹⁵ / ₁₆ (50)
8500 -48				30 (762)	45 ⁵ / ₁₆ (1150)	

IN (MM) (1) CAN BE CUT TO SIZE - SEE PRODUCT INSTALLATION INSTRUCTIONS

PARTS & COMPONENTS

See 8500 Trims & Accessories for additional items.



8000S
Regular ¹²/₃₂" (16.5 mm) cast iron strike for panic rim device. Included with 8500.

8000S-L
Low-profile ¹⁵/₃₂" (12 mm) cast iron strike for panic rim device. Includes ⁵/₆₄" (2 mm) shims.



8000DDS
Overlapping cast iron strike for double doors and paired panic exit devices only.



- Certifications**
- Conforms to ANSI/BHMA A156.3, Grade 2
 - UL listed, Panic Exit
 - UL listed, up to 90 min. Fire Exit
 - 1 Year limited warranty
- Rail Assembly**
- Steel rail assembly
 - Stainless steel assembly (32D finish)
 - Field sizable
- Handing**
- Non-handed
- Door Size**
- 30–38 x 84" (762–965 x 2134 mm)
 - 36–48 x 96" (914–1219 x 2438 mm)* – option
- (*) Panic Exit model only*
- Door Thickness**
- 1 3/4" (45.5 mm)
- Stile Width**
- 4" (106.1 mm) minimum
- Measured from door edge*
- Projection**
- 2 9/16" (65 mm) from door surface
- Vertical Rods**
- For 7' (2134 mm) doors
 - For 9' (2438 mm) door – available*
- (*) Panic Exit model only*

- Latchbolts**
- Top: stainless steel, deadlatch
 - Bottom: stainless steel
- Strikes**
- Top: steel, standard type
 - Bottom: steel, standard type
- Dogging**
- For Panic Exit models only
 - Hex key dogging
- Hardware**
- Machine and wood screws
 - Sex nut & thru-bolts¹ – available
- (1) Required for non-reinforced hollow metal doors, included with Fire Exit models*
- Electrical** —
- Options**
- Trims**
- Lever, knob, pull, and handleset trims available
- Sold separately, see 8500 Trims & Accessories*
- Finish**
- 28–Aluminum; 3–Polished brass; 32D–Satin stainless steel
- Other finishes available by special order*


8500V	32D	–	48
MODEL ¹	FINISH		OPTION

(1) SEE SELECTION GUIDE (2) OPTION: 48 –FOR DOORS 36-48X96IN (914-1219X2438MM)

SELECTION GUIDE

MODEL		DOOR SIZE ¹	DOGGING	FINISH	/CASE
8500V	Panic Exit Hardware, surface vertical rod	30-38x84 (762-965x2134)	•	28, 32D	4
8500V -48		36-48x96 (914-1219x2438)	•	28, 32D	4
8500VF	Fire Exit Hardware ² , surface vertical rod	30-38x84 (762-965x2134)	—	28, 3, 32D	4

(1) RECOMMENDED DOOR SIZE, IN (MM), FOR NON-STANDARD SIZES OR INSTALLATIONS PLEASE CONTACT. (2) FIRE EXIT HARDWARE MUST BE INSTALLED ON FIRE EXIT LABELLED DOORS.



MODEL	A	B	C	D	E ¹	F	G	H	K	M
8500V / 8500VF	2 ⁹ / ₁₆ (65)	7 ¹¹ / ₁₆ (195)	2 (50.8)	20 ¹ / ₄ (514)	33 ¹ / ₄ (845)	1 ¹⁵ / ₁₆ (50)	2 (50.8)	∅ ³ / ₈ (10)	1 ³ / ₈ (35)	5 ⁷ / ₈ (149)
8500V -48				30 (762)	45 ⁵ / ₁₆ (1150)					

IN (MM) (1) CAN BE CUT TO SIZE - SEE PRODUCT INSTALLATION INSTRUCTIONS

PARTS & COMPONENTS

See 8500 Trims & Accessories for additional items.



8000EXT96
Extension rod for 96" (2438 mm) Doors.
For #8500V Panic Exit model only.

8500TT HANDLESET TRIMS



MODEL	8503	8504	8505
Finish	28–Aluminum	28–Aluminum	28–Aluminum
Function	Passage (#3)	Storeroom (#4) ↔	Entrance (#5) ↔
Cylinder ¹	—	Threaded rim (Weiser)	Rim (Schlage C)
Projection (B)	1 13/16 (46)	1 13/16 (46)	1 13/16 (46)
Plate (HxW)	12 1/4 x 3 (311 x 76)	12 1/4 x 3 (311 x 76)	12 1/4 x 3 (311 x 76)
Pull (C)	5 5/16 (151)	5 5/16 (151)	5 5/16 (151)
Door Thickness	1 3/4 (44.5)	1 3/4 (44.5)	1 3/4 (44.5)
Warranty	1 Year limited	1 Year limited	1 Year limited

IN (MM) (1) SOLID BRASS, 6-PIN CYLINDER, 2 KEYS INCLUDED – KEYING SERVICES AVAILABLE

8500 LEVER & KNOB TRIMS



MODEL	8500FC	8500FH	8500FS	8500B
Available Functions ¹	10 Passage 70 Classroom ↔ 80 Storeroom ↔	10 Passage 70 Classroom ↔ 80 Storeroom ↔	10 Passage 70 Classroom ↔ 80 Storeroom ↔	10 Passage 70 Classroom ↔ 80 Storeroom ↔
ALL LEVERS HAVE CLUTCH RELEASE.				
Finish	26D–Satin Chrome, 3–Polished brass	26D–Satin Chrome	26D–Satin Chrome	32D–Satin stainless steel
A	ø 3 1/16 (78)	ø 3 1/16 (78)	ø 3 1/16 (78)	ø 3 1/16 (78)
B	4 5/8 (117)	4 5/8 (117)	4 5/8 (117)	ø 2 3/16 (55)
C	2 (50.8)	2 (50.8)	5/8 (16)	2 15/16 (75)
D	1 1/16 (17)	1 1/16 (17)	2 1/8 (54)	—
Door Thickness	1 3/4 (44.5)	1 3/4 (44.5)	1 3/4 (44.5)	1 3/4 (44.5)
Warranty	1 Year limited	1 Year limited	1 Year limited	1 Year limited


IN (MM) (1) KEYED FUNCTIONS INCLUDE SOLID BRASS, 6-PIN CYLINDER, SCHLAGE C CYLINDER, 2 KEYS - KEYING SERVICES AVAILABLE.

8500 SERIES

EXIT DEVICE TRIMS & ACCESSORIES

DOREX®

PULLS & PLATES



MODEL	8000NLS	8000DT	8000NL
Finish	Stainless Steel	Aluminum, painted	Aluminum, painted
Function	Night latch (#4)	Dummy pull (#2)	Night latch (#4)
Cylinder ¹	—	—	—
Projection (A)	1 3/16 (21)	1 3/16 (30)	1 3/16 (30)
Plate (HxW)	3 x 1 3/4 (36x44.5)	6 3/8 x 3 1/2 (162x89)	6 3/8 x 3 1/2 (162x89)

IN(MM) (1) RIM CYLINDER NOT INCLUDED, SOLD SEPARATELY

OTHER ACCESSORIES



8000ASAB
ASA strike filler plate.
8000BS
ASA strike and latch faceplate filler plates.



9500KTRC
Rim cylinder mounting kit.



8000EOP
Cross bore cover plate, painted steel