12 SERIES

COMMERCIAL LOCKSET



Certifications • Conforms to ANSI/NHMA A156.2, series

4000, Grade 2

• UL listed, 3hr fire-rating

Meets ADA requirements

• 1 Year limited warranty

Door Thickness • 13/8-13/4" (35-44.5mm)

Handing • Non handed

Backset • 23/4" (70 mm)

• 23/8" (60 mm) – available

• 5 " (127 mm) – available

Spring Latch • Stainless steel, ½" (12.7 mm) throw

Faceplate • Mortise type, square corners

• 11/8 x 21/4" (28.5 x 57 mm)

Strike • ASA Strike

Trim • Solid, pressure cast lever

Brass rose

• Rose diameter: 311/32" (85 mm)

Chassis • Concealed mounting plate and screws

Fixed security posts

• Lever clutch release -option

Preparation • Fits ANSI A115.2 161 door prep

• Cross bore: 21/8" (54 mm)

• Edge bore: 1" (25.4 mm)

Cylinder • Solid brass, 6-pin

• Schlage "C" keyway, 2 keys

• Removable, rekeyable

Other keyways and keying options available.

Functions 00 Dummy

70 Classroom **10** Passage 80 Storeroom 89 Exit

40 Privacy

53 Entry

Finish 26D–Satin chrome, 3–Polished brass

Other finishes available by special order

12-L	53	-C	C26D
SERIES	FUNCTION	OPTION*	FINISH


(*) -C: CLUTCH RELEASE. SEE SELECTION GUIDE FOR DETAILS.

SELECTION GUIDE

SERIES	FUNCT	ION	FINISH 1	/CASE	
12-L	00	Dummy	3, 26D	20	
12-L	10	Passage	3, 26D	10	
12-L	40	Privacy	3, 26D	10	
12-L	53	Entry ⊶	3, 26D	10	
12-L	53 C	Entry, clutch release ∽	3, 26D	10	
12-L	53 IC	Entry, SFIC, less core ⊶	26D	10	
12-L	70	Classroom •-	3, 26D	10	
12-L	70 C	Classroom, clutch release ∽	3, 26D	10	
12-L	70 IC	Classroom SFIC, less core ►	26D	10	
12-L	80	Storeroom •-	3, 26D	10	
12-L	80 C	Storeroom, clutch release ∽	3, 26D	10	
12-L	80 IC	Storeroom SFIC, less core ►	26D	10	
12-L	89	Exit •	26D	10	

⁽¹⁾ OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED.

[►] KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE.



		øΑ	В	С	D*
12-L (<u></u>	311/32	45/8	2	1/2
	(E.)	3 11/₃₂ (85)	(117)	(51)	(12.7)

IN (MM) (*) DIMENSION MAY VARY DUE TO DOOR THICKNESS.

PARTS & ACCESSORIES



9106

T-Strike, square corners: 11/8x23/4" (28.5x70 mm)

9106NH

T-Strike, no hole; square corners:

11/8 x 23/4" (28.5 x 70 mm)



ASA-T

ASA strike with adjustable tab

ASANH

ASA strike, no hole



EXT5

Backset extension to 5" (127 mm); Use with 2¾" (70 mm) backset latch



L238

Passage latch: 2%" (60 mm) backset 1%x 2%4" (28.5 x 57 mm) faceplate

SL234

Passage latch: $2\frac{3}{4}$ " (70 mm) backset $1\frac{1}{8}$ x $2\frac{1}{4}$ " (28.5 x 57 mm) faceplate



PL238

Privacy latch: 2% (60 mm) backset 11/8 x 21/4 (28.5 x 57 mm) faceplate

PL234

Privacy latch: $2\frac{3}{4}$ " (70 mm) backset $1\frac{1}{8}$ x $2\frac{1}{4}$ " (28.5 x 57 mm) faceplate



DL238

Deadlatch: 2% (60 mm) backset, $1\times2\%$ (25.4 x 57 mm) faceplate

DL234

Deadlatch: $2\frac{3}{4}$ " (70 mm) backset $1\frac{1}{8}$ x $2\frac{1}{4}$ " (28.5 x 57 mm) faceplate